

THE KAIVAC® 1250

EQUIPMENT SPECIFICATIONS

■ DESCRIPTION

Water Tank	12 Gallons (45, 42 l)
Spray Time	16 Minutes
Flow Rate	.75 GPM (2,8 l/min)
Pressure	500 psi (34,5 bars)
Vac Tank	8 Gallons (30,27 l)
See-Through Vac Tank	Yes
Dump Hose	26" (66 cm) Long
Toilet Dumping	Yes
Vac Tank Cleanout	100% @ 27 secs
Method of Dumping	Drain Hose
Vac Motor Lift	130" (330,2 cm)
Vac CFM	112 cfm (3172 l/min)
HEPA Blow Feature	300 mph (482,7 km/h)
DVD Player	Optional
HEPA Filtered Exhaust	Yes - Replaceable

■ CHEMICAL

Molded-In Chemical Holder	Gallon (1), Quart (2)
Chemical Switching	Single/Quick Change
Safety Cap System	Yes
Metering Tip Settings	5 Settings

■ ELECTRICAL

Volts (U.S.)	110 Volt - 60 Hz
Volts (Universal)	100-240V; 50-60Hz
Amps Total	14.5 amp
GFCI	Yes

■ CORDS AND HOSES

Vac Hose	35 ft. (10, 67 m) Slinky
Spray Line	32 ft. (9,75 m)
Quick-Connect Gun	Yes
Electric Cord	50 ft. (15 m)
Blow Hose	33 ft. (10 m) Slinky

■ BODY

Rotational Mold	Yes
Removable Engine Compartment	Yes - Black Box Technology
Weight	93.5 lb. (42.41 kg)
Size (H x L x W)	38" x 22" x 20" (96.5 x 55.9 x 50.8 cm)
Hard Rubber Tire	(2) 5" (12,7 cm)
Casters	(2) 4" (10,2 cm), locking
Stair Climbing Wheels	Yes
Handle	Molded-In
Parking Brake	Yes

■ TOOLS INCLUDED

Vac Wand Aluminum	2-Piece
14 Inch Squeegee Head	Yes
Blow Nozzle	Yes
Training Materials	Video and Placard
KaiBrush	Yes
Window Squeegee	Yes
Metering Tip Kit	Yes
KaiDrain	Yes
15 Gallon Tote Bag	Yes

■ WARRANTY WITH KAIVAC CHEMICAL USAGE

Body	10 Years
Parts	3 Years
Labor	1 Year



kaivac cleaning systems™

Complete Cleaning For Healthy Results™